

AN7322



Amplifier Air Management

Single or multiple shelf inlet and exhaust paths with inlet filters and re-circulation

Multiple cabinets

Designed for 600mm cabinet spacing for suite installations

De-Ice Compatible

Integrates with AN8300 de-ice systems

Easy access

Quick release door gives access to filter

Quick release flexible ducts provide instant access for servicing

Adjustable Re-circulation

Manual with preset end stop for winter position

Filter Condition Monitor

Pressure monitor with voltage free contacts

Exhaust Temperature Monitor

Preset temperature alarm. Voltage free contacts

Supply/Supply and Install

Available as hardware only or fully installed packages

GimbalCom Ltd. Specialist in Satellite System and Hot Air De-Ice Design and integration.

+44 (0) 1376 572264
sales@gimbalcom.com
www.gimbalcom.com

Wall Mounted Air Management System



Specification:

Type: AN 7322 series

Amplifiers: Klystron, TWT & SSPA units upto 3 Kw RF o/p. All major suppliers including CPI, Xicom & MCI

Max Air Flow: 500 CFM

Recirculation: Pre-set manual - adjustable stop

Filtering: Replaceable 300x300mm element

Filter Monitor: Diaphragm differential pressure gauge. Adjustable 20 to 200 pascals

Construction: Material - Alloy panels, power coat white
Fixings - Stainless steel and zinc plate

Air Ducting: Type - Rigid/Flexible - single or double skin
Material - Steel/Neoprene coated glasscloth
Fittings - Zinc plate - neoprene seal rings
Insulation - 10mm class 'O' rubber foam

Options: Colour - to customer specification
External air ducts including bird grills